

MATERIAL SAFETY DATA SHEET

EverWhite 932 Epoxy - Part C

HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	E

1. Product And Company Identification

Supplier

C-CURE
13001 SEAL BEACH BLVD.
SEAL BEACH, CA 90740 USA

Company Contact: GEORGE MARCINA
Telephone Number: 562 968 2980 Ext 103
FAX Number: 562 903 2697
E-Mail: georgem@cbpmail.net
Web Site: WWW.C-CURE.COM

Manufacturer

C-CURE
13001 SEAL BEACH BLVD.
SEAL BEACH, CA 90740 USA

Company Contact: GEORGE MARCINA
Telephone Number: 562 968 2980 Ext 103
FAX Number: 562 903 2697
E-Mail: georgem@cbpmail.net
Web Site: WWW.C-CURE.COM

Supplier Emergency Contacts & Phone Number

GEORGE MARCINA: 562 968 2980 Ext 103

Manufacturer Emergency Contacts & Phone Number

GEORGE MARCINA: 562 968 2980 Ext 103

Issue Date: 03/31/2006

Product Name: EverWhite 932 Epoxy - Part C
CAS Number: Not Established
Chemical Formula: Mixture
MSDS Number: 596
Product Code: 4F7641

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
TITANIUMDIOXIDE	13463-67-7	5 - 15
ZINCOXIDE	1314-13-2	1 - 5
SILICA, Quartz, Crystalline	14808-60-7	85 - 95

3. Hazards Identification

Primary Routes(s) Of Entry

Inhalation
Skin Contact
Eye Contact
Ingestion

Eye Hazards

May cause eye irritation.

Skin Hazards

May cause skin irritation.

Ingestion Hazards

May cause irritation of digestive tract.

MATERIAL SAFETY DATA SHEET

EverWhite 932 Epoxy - Part C

3. Hazards Identification - Continued

Inhalation Hazards

Causes respiratory tract irritation. May cause nose, throat, and lung irritation. May cause delayed lung injury.

Chronic/Carcinogenicity Effects

Contains Silica sand, known Human Carcinogen (Category 1)

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, flush skin with plenty of water. Get medical attention if irritation (redness, rash, blistering) develops and persists.

Ingestion

DO NOT INDUCE VOMITING. If victim is fully conscious, give one or two cups of water or milk to drink. Get medical attention immediately.

Inhalation

If inhaled, remove to fresh air. Consult a physician immediately if irritation persists. Do not give an unconscious person anything to drink.

5. Fire Fighting Measures

Flash Point: N/A °F

Flash Point Method: N/A

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

6. Accidental Release Measures

Avoid generating dust. Sweep up and remove immediately. Use appropriate personal protective equipment (PPE). OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS REGARDING NOTIFICATIONS OF ACCIDENTAL RELEASES.

7. Handling And Storage

Handling And Storage Precautions

Use only with adequate ventilation.

Handling Precautions

Avoid creating dust. Avoid breathing dust. Avoid contact with skin and clothing. Avoid contact with eyes.

Storage Precautions

Keep dry until ready to use.

Work/Hygienic Practices

Use good personal hygiene. Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate ventilation.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

MATERIAL SAFETY DATA SHEET

EverWhite 932 Epoxy - Part C

8. Exposure Controls/Personal Protection - Continued

Skin Protection

If hands or feet will be exposed, wear impervious gloves and/or boots.

Respiratory Protection

In case of inadequate ventilation and when exposed to dust above the recommended limits, wear a suitable NIOSH-approved respirator.

Ingredient(s) - Exposure Limits

TITANIUM DIOXIDE

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

ZINC OXIDE

ACGIH TLV-STEL 10 mg/m³

ACGIH TLV-TWA 5 mg/m³

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 5 mg/m³

OSHA PEL-TWA 15 mg/m³

SILICA, Quartz, Crystalline

ACGIH TLV-TWA 0.05 mg/m³

OSHA PEL-TWA 30/%SiO₂+2mg/m³

OSHA PEL - TWA 10/% SiO₂ +2 mg/m³

OSHA PEL-TWA 250/%SiO+5 mppcf

Cal EPA - OEHHA - REL - 3 micrograms/m³

9. Physical And Chemical Properties

Appearance

Free flowing white powder.

Chemical Type: Mixture

Physical State: Solid

Boiling Point: N/A °F

Specific Gravity: 2.7

Vapor Density: N/A

Solubility: SLIGHT

Evaporation Rate: N/A

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

Incompatible Materials

Contains Portland cement which, when wet, is highly alkali. As a result, it is incompatible with acids, ammonium salts, aluminum and other alkali and alkaline earth metals.

11. Toxicological Information

Chronic/Carcinogenicity

Contains sand, known human carcinogen.

Carcinogenicity Indicators

NTP Carcinogen

IARC Carcinogen

MATERIAL SAFETY DATA SHEET

EverWhite 932 Epoxy - Part C

11. Toxicological Information - Continued

Carcinogenicity Indicators - Continued

Ingredient(s) - Carcinogenicity

SILICA, Quartz, Crystalline

NTP - Listed On The National Toxicology Program

Listed In The IARC Monographs

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

RCRA Information

Not considered RCRA Hazardous Waste.

14. Transport Information

DOT Shipping Label

NOT REGULATED

15. Regulatory Information

SARA Hazard Classes

Chronic Health Hazard

Ingredient(s) - U.S. Regulatory Information

ZINC OXIDE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

SARA - Acute Health Hazard

SARA - Chronic Health Hazard

SILICA, Quartz, Crystalline

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

SARA - Chronic Health Hazard

State Regulations

Cal EPA - Toxic Hot Spots - OEHHA - REL - 3 micrograms /m3

Ingredient(s) - State Regulations

TITANIUM DIOXIDE

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

New York City - Hazardous Substance

ZINC OXIDE

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

Pennsylvania - Workplace Hazard

Pennsylvania - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

SILICA, Quartz, Crystalline

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

MATERIAL SAFETY DATA SHEET

EverWhite 932 Epoxy - Part C

16. Other Information

HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

Personal Protection: E

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (323) 582-0846

This MSDS Supercedes A Previous MSDS Dated: 01/13/2006

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

C-CURE

Printed Using MSDS Generator™ 2000