

# MATERIAL SAFETY DATA SHEET

## UniLayment FastSet 969, NonSanded

### HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	E

### 1. Product And Company Identification

#### Supplier

C-CURE  
13001 SEAL BEACH BLVD.  
SEAL BEACH, CA 90740 USA

Company Contact: GEORGE MARCINA  
Telephone Number: 562 968 2980 Ext 103  
FAX Number: 562 903 2697  
E-Mail: georgem@cbpmail.net  
Web Site: WWW.C-CURE.COM

#### Manufacturer

C-CURE  
13001 SEAL BEACH BLVD.  
SEAL BEACH, CA 90740 USA

Company Contact: GEORGE MARCINA  
Telephone Number: 562 968 2980 Ext 103  
FAX Number: 562 903 2697  
E-Mail: georgem@cbpmail.net  
Web Site: WWW.C-CURE.COM

#### Supplier Emergency Contacts & Phone Number

GEORGE MARCINA: 562 968 2980 Ext 103

#### Manufacturer Emergency Contacts & Phone Number

GEORGE MARCINA: 562 968 2980 Ext 103

Issue Date: 02/23/2007

Product Name: UniLayment FastSet 969, NonSanded  
Chemical Name: Mortars  
CAS Number: Not Established  
Chemical Formula: Mixture  
MSDS Number: 864  
Product Code: C55,4F8255

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
CALCIUM ALUMINATE, FUSED	65997-16-2	15 - 25
CALCIUM SULFATE	7778-18-9	5 - 15
VINYL COPOLYMER	Not Establish	1 - 5
Calcium Carbonate	1317-65-3	50 - 60
Portland Cement	65997-15-1	1 - 10

### 3. Hazards Identification

#### Primary Routes(s) Of Entry

Inhalation. Skin Contact. Eye Contact. Ingestion

#### Eye Hazards

Irritant, severe eye irritation. May cause eye injury. Effects may be delayed.

#### Skin Hazards

Contains Portland cement and exposure to dry Portland cement may cause drying of skin with consequent mild irritation.  
Prolonged contact with wet Portland cement may cause severe, potentially irreversible damage to the skin in the form of chemical (caustic) burns.

# MATERIAL SAFETY DATA SHEET

## UniLayment FastSet 969, NonSanded

### 3. Hazards Identification - Continued

#### Ingestion Hazards

Ingestion is not known to be harmful, however the product contains Portland cement which is caustic to mucus tissue and should not be consumed.

#### Inhalation Hazards

Causes respiratory tract irritation. May cause nose, throat, and lung irritation. May cause delayed lung injury.

#### Chronic/Carcinogenicity Effects

May contain small amounts of Silica sand, known Human Carcinogen (Category 1). May contain traces of chemicals on Prop 65 list.

### 4. First Aid Measures

#### Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### Skin

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

#### Ingestion

DO NOT INDUCE VOMITING. If victim is fully conscious, give one or two cups of water or milk to drink. Get medical attention immediately.

#### Inhalation

If inhaled, remove to fresh air. Consult a physician immediately if irritation persists. Do not give an unconscious person anything to drink.

### 5. Fire Fighting Measures

Flash Point: N/A °F

Flash Point Method: N/A

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

### 6. Accidental Release Measures

Avoid generating dust. Sweep up and remove immediately. Use appropriate personal protective equipment (PPE). OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS REGARDING NOTIFICATIONS OF ACCIDENTAL RELEASES.

### 7. Handling And Storage

#### Handling And Storage Precautions

Use only with adequate ventilation.

#### Handling Precautions

Avoid creating dust. Avoid breathing dust. Avoid contact with skin and clothing. Avoid contact with eyes.

#### Storage Precautions

Keep dry until ready to use.

#### Work/Hygienic Practices

Use good personal hygiene. Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

No Data Available...

# MATERIAL SAFETY DATA SHEET

## UniLayment FastSet 969, NonSanded

### 8. Exposure Controls/Personal Protection - Continued

#### Engineering Controls

Use with adequate ventilation.

#### Eye/Face Protection

Safety glasses with side shields or goggles recommended.

#### Skin Protection

If hands or feet will be exposed, wear impervious gloves and/or boots.

#### Respiratory Protection

In case of inadequate ventilation and when exposed to dust above the recommended limits, wear a suitable NIOSH-approved respirator.

#### Ingredient(s) - Exposure Limits

CALCIUM ALUMINATE, FUSED

OSHA PEL = 5 mg/m<sup>3</sup> (Respirable)

OSHA PEL = 10 mg/m<sup>3</sup> (Total)

ACGIH TLV = 5 mg/m<sup>3</sup> (Respirable)

ACGIH TLV = 10 mg/m<sup>3</sup> (Total)

CALCIUM SULFATE

TLV = 10 mg/m<sup>3</sup>

PEL = 15 mg/m<sup>3</sup> (total)

PEL = 5 mg/m<sup>3</sup> (respirable)

Calcium Carbonate

OSHA - PEL - TWA - 15mg/m<sup>3</sup>

NIOSH - REL 10 mg/m<sup>3</sup>

ACGIH- TLV - 10 mg/m<sup>3</sup>

OSHA - PEL - TWA - 5 mg/m<sup>3</sup>

Portland Cement

OSHA - PEL - 5mg/m<sup>3</sup>

OSHA - PEL - TWA - 50mppcf

ACGIH - TLV - 10mg/m<sup>3</sup>

### 9. Physical And Chemical Properties

#### Appearance

Free flowing white or gray powder.

**Chemical Type:** Mixture

**Physical State:** Solid

**Boiling Point:** N/A °F

**Specific Gravity:** 2.7

**Vapor Density:** N/A

**Solubility:** SLIGHT

**Evaporation Rate:** N/A

### 10. Stability And Reactivity

**Stability:** STABLE

**Hazardous Polymerization:** WILL NOT OCCUR.

#### Conditions To Avoid (Stability)

Avoid unintentional contact with water.

#### Incompatible Materials

Contains Portland cement which, when wet, is highly alkali. As a result, it is incompatible with acids, ammonium salts, aluminum and other alkali and alkaline earth metals.

# MATERIAL SAFETY DATA SHEET

## UniLayment FastSet 969, NonSanded

### 11. Toxicological Information

#### Chronic/Carcinogenicity

May contain small amounts of Silica sand - a known human carcinogen. May contain traces of chemicals on Prop 65 list.

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

#### RCRA Information

Not considered RCRA Hazardous Waste.

### 14. Transport Information

#### DOT Shipping Label

NOT REGULATED

### 15. Regulatory Information

#### SARA Section 313 Notification

This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

#### State Regulations

Cal EPA -Toxic Hot Spots - OEHHA - REL - 3 micrograms /m3

#### Ingredient(s) - State Regulations

Calcium Carbonate

Pennsylvania - Workplace Hazard

Portland Cement

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

### 16. Other Information

#### HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

Personal Protection: E

#### Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (323) 582-0846

This MSDS Supersedes A Previous MSDS Dated: 02/23/2007

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

C-CURE CORPORATION