



# Grouting Materials Application

Grouting Materials Application

TYPE TILE	PERFORMANCE LEVEL				GROUT AND JOINT SIZE					
	Light (Residential)	Moderate	Heavy	Extra Heavy	A SUPREME 925 <1/8" (3 mm) joint (White Only)	B MP <sup>1</sup> NONSANDED 923 CUREPERFECT <sup>2</sup> 930 <1/8" (3mm) joint (All Colors <sup>**</sup> )	C MP <sup>1</sup> SANDED 924 CUREPERFECT <sup>2</sup> 930 >1/8" (3 mm) joint (All Colors <sup>**</sup> )	D AR <sup>1</sup> SANDED 922 <1/8" (3 mm) joint (All Colors <sup>**</sup> )	E COLORSET EPOXY SYSTEM 931 & EVERWHITE <sup>2</sup> 932 up to 1/2" (13 mm) joint (Special Colors <sup>**</sup> )	F PAVERMIX 928 1/2" to 1" (13 to 25 mm) joint (All Colors <sup>**</sup> )
<b>GLASS MOSAICS</b> Interior or Exterior Walls or Floors	•				A	B			E <sup>2</sup>	
		•			A	B			E <sup>2</sup>	
			•		A	B			E <sup>2</sup>	
				•					E <sup>2</sup>	
<b>CERAMIC MOSAICS AND PORCELAIN TILES</b> Interior Walls	•				A	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
		•			A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
			•		A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•					E <sup>2</sup>	
Exterior Walls		•			A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
			•		A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•					E <sup>2</sup>	
Interior and Exterior Floors	•					B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
		•				B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
			•			B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•					E <sup>2</sup>	
<b>WALL TILES</b> Interior Walls	•				A	B			E <sup>2</sup>	
		•			A <sup>1</sup>	B	C		E <sup>2</sup>	
<b>QUARRY &amp; PAVERS</b> Interior Walls and Floors	•						C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
		•					C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
			•				C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•					E <sup>2</sup>	
Exterior Walls and Floors		•					C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
			•				C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•					E <sup>2</sup>	
<b>DIMENSION STONE*</b> Interior Walls and Floors	•				A	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
		•			A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
			•		A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•					E <sup>2</sup>	
Exterior Walls and Floors		•			A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
			•		A <sup>1</sup>	B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•					E <sup>2</sup>	
<b>ABSORPTIVE TILE &gt;7%</b> Interior Walls	•					B	C		E <sup>2</sup>	
		•				B	C		E <sup>2</sup>	
			•			B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
				•		B	C	D <sup>1</sup>	E <sup>2</sup>	F <sup>1</sup>
Interior Floors	•				B	C		E <sup>2</sup>	F <sup>1</sup>	

\* To prevent scratching of marble surfaces, use nonsanded grout only.  
 \*\* Color selection can be made from Grout Color Guide.  
 1 Mixed with PROGROUT ADDITIVE 945 in lieu of water.  
 2 For maximum strength, acid resistance or stain resistance.

Members of National Tile Contractors Association, Materials & Methods Standards Association, Ceramic Tile Distributors Association.

NOTICE: The information in this bulletin is presented in good faith, but no warranty, express or implied, is given nor is freedom from any patent. In as much as any assistance furnished by C-Cure with reference to the safe use and disposal of its products is provided without charge, C-Cure assumes no obligation or liability therefore, except to the extent that any such assistance shall be given in good faith.

**C-CURE**  
 Seal Beach, CA 90740  
 800-895-2874  
 www.c-cure.com